

2" ilevel

Model: i12

OPERATING INSTRUCTIONS

POWER ON/OFF

- Press down once on the power button. LEDs should illuminate immediately.
- Press down again while
- illuminated to turn power off.
- The unit will timeout (power off) if left untouched for 5 minutes.

HOW TO READ THE I-LEVEL

The iLevel is designed to level both vertical and horizontal surfaces by displaying a range of colors diagramed:

- Green: Level. Yellow: Approaching level.
- Red: Not level.

FRANKLIN

Turns Green When L .evel

- **REPLACING THE BATTERIES**
- Remove the battery cover by sliding the cover and lifting.
- Remove the battery and dispose of it properly. Please recycle. Replace with 1 new AA battery.
- Install battery according to
- polarity (+/-). Close battery cover by sliding the cover into place.

*MAGNETIC: Securely attaches to metallic surfaces

This device may not cause harm-ful interference. This device must accept any interference received, including interference that may cause undesired operation.



Requires 1 ł A battery. Battery included.

FRANKLIN SENSORS INC.

6675 N Pollard Lane Meridian, ID 83646 208-918-2403

www.franklinsensors.com ranklin Sensors Inc.)2024 F (

Patent No. 11,852,503 INSi12.0

Activate Your Limited Lifetime Warranty 1. Scan the QR Code 2. Enter Info 3. Warranty Activated

Did Something Go Wrong? Please call us! 208-918-2403

